
NIMH EV/HEV: PALLET SHIPPING

PACKAGING & SHIPPING INSTRUCTIONS

Manufacturers create batteries in formats most suited to their vehicles, so please review the size and shape of any electric vehicle or hybrid electric vehicle battery before shipping to make sure the shipping process is appropriate for the battery's size and shape. If you have concerns about shipping your battery in this way, please contact Cirba Solutions and we will happily assist you in finding the most appropriate shipping method for your battery.


CORRECTLY PACKAGING LITHIUM-ION EV BATTERIES



1

PREPARE SHIPMENT


Contact Cirba Solutions for recycling authorization tracking number. Begin to build shipment on sturdy 40" by 48" pallet.



2

PACKAGE PALLET

Secure to pallet with vinyl banding over topmost insulating layer.



3

ORANGE PLUG

Make sure orange plug is removed and area is protected from contact.



4

SHRINKWRAP TO PALLET

Shrinkwrap to pallet, with wrap extending down around pallet as well as the battery. Make sure enough wrap is used to prevent easy tearing of wrap.



5

LABEL & SHIP

Attach appropriate labels to outermost layer of shrink wrap or packing material.



CirbaSolutions.com • 1.800.852.8127 • CustomerService@CirbaSolutions.com

NIMH EV/HEV: PALLET SHIPPING

PACKAGING & SHIPPING INSTRUCTIONS

THESE INSTRUCTIONS MUST BE FOLLOWED EXACTLY.

Cirba Solutions has provided the following information, to the best of our abilities, in order to give guidance on how to ship Li-ion EV battery packs (cases containing the cells and/or modules) from your facility to ours in the safest manner possible.

We highly advise that lineman's gloves/high voltage gloves are used during handling. Gloves should be rated up to the capacity of any electrical equipment you handle; we use 1,000 volt rated gloves at Cirba Solutions.

Transport in a manner to prevent short circuits and that prevents movement, shifting, or damage.

WARNING

The wires of these battery cases can transmit high voltage electricity, even when the service plug is removed and/or the power switch set to off. This is very important to understand when shipping these batteries to prevent pinch points (meaning the wires becoming pinched, which can cause overheating), short-circuiting, and especially injury.

TAPE TERMINALS/EXPOSED WIRES

Tape all exposed, non-recessed, terminals and/or exposed wires. Non-conductive approved electrical tape must be used when taping exposed terminals and wires.

TAPE WIRES

Tape/zip tie/secure the wires, to the battery case, in a manner to prevent pinch points and/or short circuits during transportation. Non-conductive approved electrical tape must be used when taping exposed terminals and wires.

PALLETS

EV battery packs should never be stacked on top of each other. It is acceptable to place multiple same or similar-size batteries in a single layer on a pallet if they are properly secured. Pallets should not exceed 40"x 48" if possible.

DIVIDE BATTERIES

Place non-conductive material between the batteries to ensure the separation of battery cases. Cirba Solutions suggests thick cardboard.

STACKING

Stacking should only be done if batteries are crated or cocooned.

The regulations require a "Strong, rigid, outer packaging or the batteries" which can be interpreted as the battery housing itself.

COVER

Place nonconductive material on top of entire layered unit, usually a piece of cardboard satisfies most transportation carriers requirements. It is important to protect the shipment from the elements.

STRAP LAYERS

Strap all the layers together. Do not use metal strapping. Use nonconductive strapping ONLY. We suggest at least 4 straps: 2 straps perpendicular (90 degrees) from the other 2 straps. Important Note: These straps should prevent all batteries, on all layers, from moving freely.

PLASTIC WRAP (FOR PALLETIZED BATTERIES)

Generously wrap the layered batteries from top to bottom. If you can stick a finger easily through the wrap, more is needed.

This information is interpreted directly from the Transportation code, contained in Title 49. Please refer to that code for more detailed info on the shipping of batteries according to the U.S.D.O.T.

DAMAGED LITHIUM-ION BATTERIES

If the battery (or batteries) is not intact, Cirba Solutions may not be able to accept the shipment if it is determined to be hazardous waste. Cirba Solutions does not ship or receive hazardous waste. If the battery is damaged, but is still considered "intact," Cirba Solutions may request photos and will work with customers on an as needed basis for shipping solutions that may be in addition to those listed above.

If needed, hazardous waste/environmental service companies with a national footprint:

www.stericycle.com

www.hazardouswasteexperts.com/

